



DBRED RUBBER 01

ANTIVIBRATION HANGERS

DBRED RUBBER 01 Antivibration hangers

<p>APPLICATIONS FIELDS</p>	<ul style="list-style-type: none"> · Machinery antivibration support. · Suspension of machinery (air conditioning units, ventilators, etc.). · Suspension of soundproof suspended-ceiling with boards. · Antivibration solution for light weight machinery. 												
<p>INSTALLATION</p>	<p>Multipurpose antivibration hangers.</p> <p>It can be bored into the floor with a dowel, or suspended with a steel hanger and a screw \varnothing 8 mm, fixed to the slab. Thanks its design, dBred Rubber 01 provides great deflection but small load, and a better antivibration performance. The anchoring screw of the suspension mount must be perpendicular to the surface. The weight of the machine must be applied on the upper surface of dBred Rubber 01. With Rubber 01 it is possible to obtain a natural frequency of 15 Hz.</p>												
<p>WARNINGS</p>	<ul style="list-style-type: none"> · Do not screw tight the holding screw . · The screw and the nut must not compress any elastic part. · Don't forget to put the Rubber 01 neck through the hole and to place the elastic washer on the metal base. 												
<p>MAXIMUM LOAD</p>	<p>20 kg</p> <p style="text-align: center;">STATIC DEFLECTION</p> <table border="1"> <caption>Static Deflection Data</caption> <thead> <tr> <th>Deflection (mm)</th> <th>daN</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>7</td> </tr> <tr> <td>2</td> <td>12</td> </tr> <tr> <td>3</td> <td>20</td> </tr> <tr> <td>4</td> <td>28</td> </tr> <tr> <td>5</td> <td>35</td> </tr> </tbody> </table>	Deflection (mm)	daN	1	7	2	12	3	20	4	28	5	35
Deflection (mm)	daN												
1	7												
2	12												
3	20												
4	28												
5	35												

All the indications provided in this technical sheet are purely approximate and not binding for legal purpose. The data listed has been gathered from laboratory test and it hence follows that in practical applications on building sites the final products may be subject to variations depending on meteorological conditions and the installation. The user must always check suitability of the product for its specific use, undertaking all liability implicit in and deriving from use of the product, as well as comply with all methods and instruction for use generally referable to "workmanlike" execution. Edilteco S.p.A reserves the right to change the contents of this mechanical data sheet on its final judgment. The spreading of this data sheet through any media, supersedes and cancels the validity of any other technical data sheet previously published.



dBred Noise Reduction Division

DS DBRED RUBBER 01 . Rev 02/2018 .GB



Edilteco S.p.A. Via dell'Industria, 710 . 41038 San Felice sul Panaro (MO) Italy
Ph. +39 0535 82161 . Fax +39 0535 82970 . www.edilteco.com | info@edilteco.com

© Copyright EDILTECO S.p.A. - Non authorized reproduction is forbidden.



COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =