= ISO 9001 =



# DECLARATION OF PERFORMANCE (Reg. EU 305/2011) n. EDI01/2013

1. Unique identification code of the product-type:

#### **ISOLTECO**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

#### **ISOLTECO**

**3.** *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:* 

### Thermal rendering / plastering insulting mortar

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

EDILTECO S.p.A., Via dell'Industria, 710 - 41038 San Felice sul Panaro (MO) Italy ## +39 0535 82161 - Fax +39 0535 82970 - e-mail: edilteco@edilteco.it - www.edilteco.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

### Not Applicable

**6.** System or systems of assessment and verification of constancy of performance of the construction product as ser out in the Annex V:

#### System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

UNI EN 998 – 1: 2010 "Specification for mortar for masonry. Part 1: rendering and plastering mortar"



Edileco S.p.A.
Via dell'Industria, 710
41036 San Felice s/P (MO) Italy
tel. +39 0535 82161
fax. +39 0535 82970
e-mail: info@edilteco.it
www.edilteco.it
Cod. Fisc./Part, IVA: 01039233360
Cap. Soc. Sottoscritto € 1.170.00,00
versato € 842,500,00





## AZIENDA CON SISTEMA DI GESTIONE QUALITÀ CERTIFICATO DA DNV

= ISO 9001 =



**8.** In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

## Not Applicable

## 9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2 s1 d0	
Adhesion	0,13 N/mm2	
Capillary water absorption	W1	
Water vapour permeability coefficient	$\mu = 9$	
Thermal conductivity	λd 0,058 W/mK	UNI EN 998-1 : 2010
Durability	Against freeze/thaw: evaluation based on provisions valid in the intended place of use of the mortar	
External fire performance	NPD	
Noise absorption	Rw 0 42dB; ∆Rw 7dB	
Emissions of dangerous substances	NPD	
Resistance to fire	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :
Erika Preti,
Edilteco Quality Manager
San Felice sul Panaro, 01/07/2013.





Edilteco S.p.A.
Via dell'Industria, 710
41038 San Felice s/P (MO) Italy
tel. +39 0535 82161
fax. +39 0535 82161
e-mail: info@edilteco.it
www.edilteco.it
Cod. Fisc./Part. IVX: 01039233690
Cap. Soc. Sottoscritto € 1.170.00,00
versato € 842.600,00



