
PIPES AND STEEL BENDS

METAL PIPES FOR PUMPING LIGHTWEIGHT SCREEDS

PIPES AND STEEL BENDS Metal pipes for pumping lightweight screeds		
CHARACTERISTICS	Accessories for Politerm Machine® , which: Increase the pumping efficient distance. Eliminate the risks of the possible explosion of the rubber pipes and the relative consequences. Eliminate the constipation of the mortar, caused by the elongation and the relaxation of the rubber pipes. Accelerate the application on site, achieving the upper floors. Are economical.	
TECHNICAL CHARACTERISTICS	· Material:	galvanized steel
	· Pipes length:	3 m each
	· Pipes diameter:	60 mm
	· Bends:	90° and 45°
	· Junction's flange:	compatible with the flanges of the Politerm Machine® and the flanges of the normal rubber pipes
	· Fixing rings:	for the hooking to the building site's scaffoldings

All the indications provided in this technical data sheet are purely approximate and not binding for legal purpose. The data listed has been gathered from laboratory tests and it hence follows that in practical applications on building sites the final characteristics of the products may be subject to substantial variations depending on the meteorological conditions and the installation. The user must always check suitability of the product for its specific use, undertaking all liability implicit in and deriving from use of the product, as well as comply with all methods and instructions for use generally referable to "ownkmanlike" execution. Editlects O. S.A. reserves the right to change the contents of this mechanical data sheet on its final judgements. The spreading of this data sheet through any media, supersedes and cancels the validity of any other technical data sheet previously published.







2. STEEL BENDS FOR POLITERM MACHINE®











E&MP Engineering Machines Plants Division

DS PIPES AND STEEL BENDS . Rev 07/2016 . GB









