

Electrical power supply

GUM GUM MACHINE

MIXING AND PUMPING MACHINE FOR THE APPLICATION OF ACOUSTIC INSULATING RUBBER COMPOUND

GUM GUM MACHINE

Mixing and pumping machine for the application of acoustic insulating rubber compound

TYPE OF EQUIPMENT

TECHNICAL CHARACTERISTICS

Compact, modular and easily transportable mixer for easy handling and application on job site. Specific system for pumping and spraying rubber compound, for the acoustic insulation of floors, stairs and walls. Suitable for the spraying of lightweight plasters (type Isolteco® 150 and Isolteco® 230) and self-levelling mortars.

Power supply:	Three phase 380 - 400 V / 50 Hz
Power used required:	3,32 kW
Pump-rotor type:	Long pitch (type D8-1,5)
Pump yield:	26 L/min
Pumping distance:	20 m
Mixer-hopper usable volume:	$50 \div 60 L (1 \text{ bag with additive})$
Dimensions:	1240 x 560 x 1200 mm
Pump + mixer weight:	86 + 48 kg
Standard pipe used:	15 + 5 m, Ø 25 + lever connections included + air pipes 20 m

All the indications provided in this technical sheet are purely approximate and not binding for legal purpose. The data listed has been gathered from laboratory test and it hence follows that in practical applications on building sites the final products may be subject to variations depending on meteorological conditions and the installation. The user must always check suitability of the product for its specific use, undertaking all liability implicit in and deriving from use of the product, as well as comply with all methods and instruction for use generally referable to "workmanlike" execution. Edilteco S.p.A reserves the right to change the contents of this mechanical data sheet on its final judgment. The spreading of this data sheet through any media, supersedes and cancels the validity of any other technical data sheet previously published.











E&MP Engineering Machines Plants Division



