

STRIPS DBRED LF5

ADHESIVE "L" SHAPED PERIMETER STRIPS
ACCESSORY FOR IMPACT SOUND INSULATION



STRIPS DBRED LF5					
Adhesive "L" shaped perimeter strips - Accessory for impact sound insulation					
DESCRIPTION	Expanded polyethylene adhesive strips with hot creasing to facilitate folding into an "L" shape.				
COMPOSITION	Closed-cell expanded polyethylene.				
COLOUR	White.				
FIELDS OF APPLICATION	"L" shaped adhesive strip to be applied after laying the impact sound insulating mat in the floating screed system; trim only after the floor covering has been installed.				
THICKNESS	5 mm				
PACKAGING	PRODUCT	HEIGHT cm	ROLL LENGTH EACH m	PACKAGING ROLLS EACH n°	QUANTITY PACKAGES EACH m
	DBRED LF5 10+5	10+5	50	10	500
	DBRED LF5 15+5	15+5	50	7	350
TECHNICAL CHARACTERISTICS	CHARACTERISTIC			VALUE	NORM
	Density:			23 kg/m ³	-
	Thermal conductivity:			0,04 W/mK	-
	Maximum service temperature:			-20 °C / +80 °C	-
	Compressive stress at 10% deformation:			24 kPa	ISO 7214
All the indications provided in this technical data sheet are purely approximate and not binding for legal purposes. The data listed has been gathered from laboratory tests and it hence follows that in practical applications on buildings sites the final characteristics of the products may be subject to substantial variations depending on the meteorological conditions and the installations. The user must always check suitability of the product for its specific use, undertaking all liability implicit in and deriving from use of the product, as well as comply with all the methods and instructions for use generally referable to "workmanlike" execution. Edilteco S.p.A. reserves the right to change the contents of this technical data sheets on its final judgements. The spreading of this data sheet through any media, supersedes and cancels the validity of any other technical data sheet previously published.					