GUM GUM MACHINE

MIXING AND SPRAYING MACHINE FOR GUM GUM SPRAY, CREATES RUBBER LAYERS FOR ACOUSTIC INSULATION

CE

GUM GUM MACHINE
Simple, fast, clean and effective - Single-phase 220 V power supply

TYPE OF EQUIPMENT	Lightweight, easy-to-handle and flexible mixing machine. Allows easy transport and movement on site. Designed for pumping and spraying special pre-mixed rubber-based compound for the acoustic insulation of floors, stairs, and walls. Also suitable for spraying lightweight plasters (Isolteco® 150 and Isolteco® 230) and self-levelling mortars.	
	CHARACTERISTIC	**VALUE**
	Electric motor:	Sprayer: 1.5 kW - 220 V
		Mixing tank: 1.1 kW - 220 V - 50 Hz
	Flow rate *:	0,5 ÷ 12 L/min.
	Max grain size:	5 mm
	Max pressure:	35 bar
	Compressor:	210 L/min. (optional)
TECHNICAL CHARACTERISTICS	Stainless steel hopper capacity:	Sprayer: 50 L
		Mixing tank: 50 L effective - 70 L nominal
	Spray distance *:	40 m
	Spray height *:	15 m
	Loading height:	65 cm
	Outlet nozzle:	Ø 25 mm
	Dimensions (L x W x H):	1200 x 630 x 700 mm
	Weight:	80 kg

* The performance data may vary depending on the viscosity, quality, and composition of the mix, wear of the pump, hose diameter, and pipe length. Maximum height and distance cannot be achieved simultaneously.