





# ISOLCAP MIXER 50

COMPACT MIXER

ISOLCAP MIXER 50 Compact mixer		
TYPE OF EQUIPMENT	Isolcap Mixer 50 is a compact mixer, lightweight and silent, ideal to be used in small building sites and for refurbishment works.	
TECHNICAL CHARACTERISTICS	Tank capacity:	56 L
	Yield:	47 L
	Tank Ø:	580 mm
	N° blade turns:	55 rpm
	Electrical engine power:	0.55 kW
	Absorption:	5 A
	LpA operator position:	59 dB(A)
	Machine weight (packaging):	30 (32) kg
	Dimensions - width / length / height (packaging):	580/630/795 (585/620/455)
STANDARD EQUIPMENT	<ul style="list-style-type: none"> <li>· Electrical safety limit switch.</li> <li>· Switch with minimum tension reel IP55 and plug IP67.</li> <li>· Handle.</li> <li>· 2 plastic tanks, suitable for low temperatures.</li> <li>· 1 blade for lightweight premixed mortars.</li> <li>· Carton packaging.</li> </ul>	
OPTIONAL ACCESSORIES	<ul style="list-style-type: none"> <li>· 1 blade for heavy premixed mortars.</li> <li>· Kit of circuit breaker</li> <li>· 5 tanks kit</li> </ul>	
TYPES OF BLADES AND USE	 <p><b>USE OF LIGHTWEIGHT PREMIXED MORTARS:</b> With the machine turned on, pour the bag into the tank and add the mixing water. Mix until to obtain a perfect mixing (see the technical datasheets of the products).</p>	 <p><b>USE OF HEAVY PREMIXED MORTARS:</b> with the machine turned off, pour all the mixing water necessary for the correct mixing (see the technical datasheets of the products), then, turn on the machine and add the bag to be mixed.</p>
	WARNINGS	At the end of the work, clean properly the equipment with clean water.
<p>All the indications provided in this technical sheet are purely approximate and not binding for legal purpose. The data listed has been gathered from laboratory test and it hence follows that in practical applications on building sites the final products may be subject to variations depending on meteorological conditions and the installation. The user must always check suitability of the product for its specific use, undertaking all liability implicit in and deriving from use of the product, as well as comply with all methods and instruction for use generally referable to "workmanlike" execution. Edilteco S.p.A reserves the right to change the contents of this mechanical data sheet on its final judgment. The spreading of this data sheet through any media, supersedes and cancels the validity of any other technical data sheet previously published.</p>		



E&MP Engineering Machines Plants Division

DS ISOLCAP MIXER 50 . Rev 08/2018 . GB



Edilteco S.p.A. Via dell'Industria, 710 . 41038 San Felice sul Panaro (MO) Italy  
Ph. +39 0535 82161 . Fax +39 0535 82970 . [www.edilteco.com](http://www.edilteco.com) | [info@edilteco.com](mailto:info@edilteco.com)

© Copyright EDILTECO S.p.A. - Non authorized reproduction is forbidden.

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =