

UNDERLAY, IN ROLLS, FOR IMPACT SOUND INSULATION

DBRED FONOTECH					
Ur	nderlay, in rolls	s, for impa	act sound i	insulation	

COMPOSITION Chemically crosslinked polyethylene foam. **COLOUR** Dark grey. FIELDS OF APPLICATION Under screed. **THICKNESS** 4 * - 5 - 10 * mm

PRODUCT ROLL DIMENSIONS **QUANTITY PER ROLL** PALLET WEIGHT FONOTECH 4* 150 x 6000 cm 90 m² ~ 64 kg **PACKAGING FONOTECH 5** 150 x 1500 cm 22,5 m² ~ 47 kg FONOTECH 10 * $150 \times 5000 \text{ cm}$ $75 \, m^2$ $\sim 92 \text{ kg}$ **APPLICATION** Contact our Edilteco Technical Department

	CHARACTERISTIC	VALUE	NORM	
	Density:	~ 30 kg/m³	UNI EN ISO 845	
	Tensile strength:	Longitudinal: 0,31 MPa	UNI EN ISO 1798	
		Transversal: 0,29 MPa		
	Elongation at break:	Longitudinal: 124,63%	UNI EN ISO 1798	
		Transversal: 112,83%		
TECHNICAL	Deformation under compression force:	10%: 0,028 MPa	UNI EN ISO 3386	
CHARACTERISTICS		25%: 0,055 MPa		
		50%: 0,164 MPa		
	Water absorption:	2,0%	UNI EN 12087	
	Thermal conductivity $\lambda_{\scriptscriptstyle D}$:	0,0320 W/mK	UNI EN 12667	
	Impact sound insulation ΔL_{w} :	thick. 4 mm: 32 dB		
		thick. 5 mm: 33 dB	UNI EN ISO 140-7/8 **	
		thick. 10 mm: 36 dB		

All the indications provided in this technical data sheet are purely approximate and not binding for legal purpose. The data listed has been gathered from laboratory tests and it hence follows that in practical applications on building sites the final characteristics of the products may be subject to substantial variations depending on the meteorological conditions and the installation. The user must always check suitability of the product for its specific use, undertaking all liability implicit in and deriving from use of the product, as well as comply with all methods and instructions for use generally referable to "workmanlike" execution. Edilteco S.p.A. reserves the right to change the contents of this mechanical data sheet on its final judgements. The spreading of this data sheet through any media, supersedes and cancels the validity of any other technical data sheet previously published.

* Available on demand. / ** Corresponding to the current UNI EN ISO 16283-2 and UNI EN ISO 10140-3.



