

OVERLAPPED COUPLED UNDERLAY, IN ROLLS, FOR IMPACT SOUND INSULATION

Overlapped coupled underlay, in rolls, for impact sound insulation
Chemically crosslikend expanded PE, 5 mm thickness, coated with reflective aluminated film, joint to polyester fiber 6 mm and with side 50 mm overlaps.

**COLOUR** Anthracite - white.

FIELDS OF APPLICATION Under screed.

**THICKNESS** ~ 11 mm

COMPOSITION

PACKAGING	ROLL DIMENSIONS	QUANTITY PER ROLL	
	150 x 1000 cm	15 m <sup>2</sup>	

**DBRED FONOTECH 5.6 ANTISCRATCH** 

**APPLICATION** Contact our Edilteco Technical Department.

	CHARACTERISTIC	VALUE	NORM	
	Density:	~ 30 kg/m³ *	UNI EN ISO 845	
	Tensile strength:	Longitudinal: 0,31 MPa *	UNI EN ISO 1798	
		Transversal: 0,29 MPa *		
	Elongation at break:	Longitudinal: 124,63% *	UNI EN ISO 1798	
		Transversal: 112,83% *		
TECHNICAL	Deformation under compression force:	10%: 0,028 MPa *	UNI EN ISO 3386	
CHARACTERISTICS		25%: 0,055 MPa *		
		50%: 0,164 MPa *		
	Water absorption:	2,0% *	UNI EN 12087	
	Thermal conductivity $\lambda_{_{D}}$ :	0,0320 W/mK*	UNI EN 12667	
	Impact sound insulation $\Delta L_{w}$ :	36 dB **	UNI EN ISO 140-7/8 UNI EN ISO 717-2	
	Compressibility c:	CP2	UNI EN ISO 12431	

\* Value based on expanded PE / \*\* Screed 5 cm - 100 kg/m<sup>2</sup>.



